

3 3/8" wind pressure
Pitch ~ 4/5 semitone sharp

OOSTHUIZEN 4/30/74
PRESTANT 6'

1	2	3	4	5	6	7	8
wind wg/low lip thick	ϕ	mw	toe hole	lang. thick	lang. thin	metal thick bottom/top	lengths body foot
FF	94.0	insoldered 23.0					Embossed
GG	80.4	22.3	65.7	10.7	2.0	75° 1.75	1.10/535 270 4 nicks, upper lip sort of blunt
AA	86.0	insoldered 18.8					
#	78.0	21.2					
B		19.5					
C	71.0	19.4	57.6	10.3	2.0	~68° 1.1	1.75 1135 173 11 nicks, gageph, blunt upper
#							
D	67.0	17.3					
#							
E	67.0	16.0					Embossed
F							
#	55.8	15.4	50.0	16.8	2.5	60° 1.2	.8 780 7 nicks, gageph
G							
#	52.0	insoldered 14.0					Foot embossed
A							
#	49.0	12.0					
B							
C	~1.2	45.6	13.0	37.2	10	1.7 ~67	.95 7 552 185 6 nicks, good pipe, hammered
#							
D		43.0					
#							
E		39.4					
F							
#	~1.0	39.5	10.4	30.0	16.4	1.7 ~69	.85 387 344 56 nicks embossed pipe gagephase
G							
#		34.0					
A							
#		31.0					
B							
C		31.0					
#		Damaged pipe					Embossed
D	~1.3	31.2	7.8	22.8	6.1	1.7 69°	.65 .5 235 400 several nicks gagephase
#							
E		25.6					
F							
#		21.4					
G		21.0					
A	~1.0	21.0	6.0	16.9	6.0	1.7 ?	.6 ? 152 487 3 nicks largest nicks damaged - top scraped away

4-30-74

ОСТААФ 4'

[illegible]

4-30-74

WOUDFLUIT 2'

	1	2	3	4	5	6	7	8		
	ϕ	mW	M	toe hole	Lang thickn	Lang. L	wind way / low lip thickness	Metal thick. Bottom Top	length Body	REMARKS
1										
2	AA#	36.0	28.0	8.8	5.5	2.0	75°	.6 .60	.5 291	Looks like made from 2 pipes Gegenphase. No nicks
3										
4	E°	38.0	26.0	8.6	7.0	1.5	70°	1.0 .80	.85 250	Same flat as front pipe
5										
6	e'	20.8	16.0	5.1	6.0	1.5	72°	1.0 .55	.65 95	Dubbed flat. No nicks.
7										
8	e ²	13.0	8.7	2.4	4.3	1.0	70°	0.7 .35	— 43	Orphan pipe. Dubbed flat
9										
10										
11										
12										
13										
14										
15										
16										
17										
18										
19										
20	MIXTURE 1 1/2'									
21	FF	27.6	22.0	8.0	6.6	1.4	70°	1.2 .70	.50 265	Dubbed Good pipe. Rounded lower Pipe
22										
23	C°	20.5	16.0	6.3	5.4	1.0	80°	1.5 1.00	.70 177	Dubbed flat
24										
25	G#°	14.4	11.5	4.6	6.8	0.9	80°	1.5 .65	.40 114	Dubbed. No nicks Good pipe
26										
27	g#'	10.0	7.8	2.8	5.0	0.7	60°	1.2 .30	— 34	Good pipe. Dubbed
28										
29	c ²	9.7	7.0	2.9	5.0	0.6	45°	1.2 .35	— 43	Good pipe. Dubbed
30										
31	QUINT 2 1/2'									
32	AA#	36.0	28.0	8.6	5.7	1.2	60°	1.1 .55	.55 400	Niehoff mouth. Gegenphase
33										
34	d'	21.4	15.5	5.0	6.0	1.8	60°	1.3 .55	.50 150	Dombedos flat Orphan large gegenphase
35										
36	f#'	15.2	13.3	4.0	5.8	1.5	69°	1.3 .60	.50 128	In soldered lip Octav-y. No gegen. Dubbed
37										
38	f#"	10.0	8.5	2.9	4.0	0.8 rounded		1.8 .4	— 63	Good pipe. Dubbed
39										
40										